

MIT510/2

5 kV Insulation Resistance Tester



- CAT IV 600 V
- Mains or battery powered
- Digital/Analogue backlit display
- Selectable test voltage from 250 to 5000 V
- Automatic IR test
- Measures to 15 TΩ
- Complete with calibration certificate

DESCRIPTION

The new 5 kV insulation resistance testers from Megger are designed specifically to assist you with the testing and maintenance of high voltage electrical equipment. The case is incredibly rugged and easy to carry, being made of tough polypropylene and achieving an ingress protection rating of IP65. In addition, the model number is marked on both sides of the case for ease of identification in stores or vehicles.

The instrument has a large easy to read backlit LCD display making it equally suitable for use in both bright sunlight and poorly lit environments. Information displayed includes resistance, voltage, leakage current, capacitance, battery status and time constant. In addition, the elapsed time of the test is displayed constantly removing the need for separate timers.

The instrument can test when being powered by the mains or its internal rechargeable battery, a great benefit when site conditions are unknown or long term testing is required.

The controls of the instrument are clear and unambiguous and a "quick start" guide is included in the lid of the instrument removing the need to carry bulky manuals under site conditions.

The instrument is fitted with a guard terminal to enhance accuracy. The guard test lead is included as standard with the instrument.

To further enhance the flexibility of the instrument the MIT510/2 has the facility to set the test voltage in steps from 250 V to 5000 V avoiding the expense of several insulation resistance testers to meet your application needs.

The IR tester is designed to meet the highest safety standards and meets the requirements of EN61010. In addition, the instrument measures the voltage at the terminals and if this is above 50 V then the instrument will display the high voltage warning and inhibit testing. At the end of the test the instrument will automatically discharge the energy transferred to the equipment during the test phase.

SPECIFICATIONS

Voltage input range

85-265 V rms, 50/60 Hz, 60 VA

Battery life

Typical capacity is 6 hours continuous testing at 5 kV with a 100 M Ω load

Test voltages

250 V, 500 V, 1000 V, 2500 V, 5000 V

Accuracy (23°C, 5 kV)

±5% @ 1 TΩ
±20% @ 10 TΩ

Guard

2% error guarding 500 kΩ leakage with 100 MΩ load

Display range

Digital display (3 digits) 10 kΩ to 15 TΩ
Analogue display 100 kΩ to 1 TΩ

Short circuit/charge current

3 mA @ 5 kV

Capacitor charge time

<3 seconds per μF at 3 mA to 5 kV

Capacitor discharge time

<120 ms per μF to discharge from 5000 V to 50 V

Capacitance measurement (above 500 V)

10 nF to 50 μF (dependent on test voltage)

Capacitance measurement accuracy (23°C)

±5% ±5 nF

Voltage output accuracy (0°C to 30°C)

+4%, -0% ±10 V of nominal test voltage at 1 GΩ load

Current measurement range

0.01 nA to 5 mA

Current measurement accuracy (23°C)

±5% ±0.2 nA at all voltages

Interference rejection

1 mA rms per 250 V test voltage up to a maximum of 2 mA

Timer range

Counts up to 99 minutes from start of test

Test regimes

Auto IR

Operating temperature

-20°C to 50°C

Storage temperature

-25°C to 65°C

Ingress protection (lid closed)

IP65

Humidity

90% RH non-condensing at 40°C

Safety

Meets the requirements of IEC61010-1 CATIV 600 V

EMC

Meets the requirements of IEC61326-1

Dimensions

305 x 194 x 360 (mm) (12 x 7.6 x 14.2 inches)

Weight

6.75 kg (15lb) approx

ORDERING INFORMATION

Item (Qty)	Order Code	Item (Qty)	Order Code
5 kV insulation resistance tester	MIT510/2		
Included Accessories			
3 m lead set, medium size insulated clips	6220-820	Control circuit test lead set	
User guide on CD-ROM	2000-213	2 x 3 m with small insulated clips	6220-822
Optional Accessories			
HV test lead sets			
3 x 3 m with un-insulated small clips	8101-181	Screened HV test leads	
3 x 8 m with un-insulated small clips	8101-182	1 x 3 m, with 5 kV screened un-insulated small clips	6220-835
3 x 15 m with un-insulated small clips	8101-183	1 x 15 m, with 5 kV screened un-insulated small clips	6311-080
3 x 10 m with medium insulated clips	1000-441		
3 x 15 m with medium insulated clips	1000-442		
3 x 3 m with large insulated clips	6220-811		
3 x 10 m with large insulated clips	1000-443		
3 x 15 m with large insulated clips	1000-432		

UK
Archcliffe Road, Dover
CT17 9EN England
T (0) 1 304 502101
F (0) 1 304 207342

UNITED STATES
4271 Bronze Way
Dallas, TX 75237-1019 USA
T 1 800 723 2861
T 1 214 333 3201
F 1 214 331 7399

OTHER TECHNICAL SALES OFFICES
Norristown USA, Sydney AUSTRALIA,
Toronto CANADA, Trappes FRANCE,
Kingdom of BAHRAIN, Mumbai INDIA,
Johannesburg SOUTH AFRICA, Conjure
THAILAND, Täby SWEDEN, Oberursel
GERMANY, Aargau SWITZERLAND

ISO STATEMENT
Registered to ISO 9001:2000 Cert. no. Q 09250
Registered to ISO 14001-1996 Cert. no. EMS 61597
MIT510_2_DS_en_V05
www.megger.com
Megger is a registered trademark